



Tr 9

RYCHLÉ TYRISTORY

Typ	Mezní hodnoty					$U_{(BO) \min}$ V	$I_D \max$ mA	při U_D V	$I_H \max$ mA	$I_{GT \max}$ mA	$U_T \max$ V	$t_q \max$ μs	Pouzdří
	$I_{TAV} A$	$I_{TRM} A$	$I_{TSM} A$	$U_{DRM} V$	$U_{RRM} V$								
PRO ROZKLADOVÉ OBVODY V TELEVIZNÍCH PŘIJÍMAČÍCH													
KT119A	3,2	30	50	750	—	800	1,5	750	100	40	2,5	3,0	Tr9
KT120A	3,2	30	50	750	—	800	1,5	750	100	40	2,5	5,0	Tr9
PRO SPINACÍ A ŘÍDICÍ OBVODY													
KT120/500	3,2	30	50	500	—	550	1,5	500	100	40	3,0	30	Tr9
PRO SÍŤOVÉ NAPÁJECÍ ZDROJE													
KT110	3,2	30	50	750	750	—	1,5	750	50	40	3,0	40	Tr9
KT110/200	3,2	30	50	200	200	—	1,5	200	50	40	3,0	40	Tr9
KT110/400	3,2	30	50	400	400	—	1,5	400	50	40	3,0	40	Tr9
KT110/600	3,2	30	50	600	600	—	1,5	600	50	40	3,0	40	Tr9